



Zs22 series dimensions in millimeters (mm)

	a	b	c	d	e	f	g	i	j
ZS2205	15.8	20.4	27.9	3	11	7	38.4	12	29.1
ZS2209	22.1	26.6	27.9	3	11	7	44.4	12	35.5
ZS2213	26	30.5	27.9	3	11	6	47.5	12	39.3

Zs22 series technical specifications and suggestions

	ZS2205-34	ZS2205-38	ZS2209-24	ZS2209-30	ZS2213-18	ZS2213-22
Weight	32.6 g	32.6 g	45.4 g	45.4 g	59.7 g	59.7 g
Winding	34T	38T	24T	30T	18T	22T
Resistance	0.164 Ohm	0.207 Ohm	0.122 Ohm	0.161 Ohm	0.082 Ohm	0.116 Ohm
IO (@10V)	0.46 A	0.4 A	0.5 A	0.45 A	0.58 A	0.46 A
KV	1587 rpm/V	1430 rpm/V	1165 rpm/V	950 rpm/V	1042 rpm/V	862 rpm/V
Typical Current	5A~10A	4A~9A	8A~14A	7A~13A	12A~20A	10A~17A
Max Current	15A	13A	19A	17A	25A	21A
Max Power	115 Watts	100 Watts	210 Watts	190 Watts	280 Watts	240 Watts
G3 LiPo Light	CX 450	CX 450	CX 850	CX 850	VX 1100	VX 1100
G3 LiPo Duration	CX 850	CX 850	CX 1100	CX 1100	CX 2100	CX 2100
Atlas ESC Suggested	12A	12A	12A/25A	12A/25A	25A	25A
Replaces "Z"	Z2205-34	Z2205-38	Z2209-26	Z2209-32	Z2213-16/20	Z2213-20/24