



ZS30 Series - Technical Specifications and Suggestions								
	3009-20	3014-12	3014-14	3020-08	3020-10	3025-06	3025-08	3025-10
Weight	98.5 g	126.3 g	126.3 g	161.7 g	161.7 g	197.6 g	197.6 g	197.6 g
Winding	20T	12T	14T	8T	10T	6T	8T	10T
Resistance	0.033 Ohm	0.019 Ohm	0.027 Ohm	0.013 Ohm	0.019 Ohm	0.008 Ohm	0.014 Ohm	0.019 Ohm
IO (@10V)	0.92 A	1.43 A	1.12 A	2.03 A	1.48 A	3.37 A	2.2 A	1.61 A
KV	1100 rpm/V	1132 rpm/V	972 rpm/V	1135 rpm/V	922 rpm/V	1287 rpm/V	970 rpm/V	775 rpm/V
Typical Current	18A~26A	24A~40A	22A~36A	36A~52A	32A~45A	45A~80A	34A~55A	30A~45A
Max Current	34A	52A	42A	70A	56A	110A	75A	65A
Max Power	450 Watts	750 Watts	600 Watts	1050 Watts	850 Watts	1500 Watts	1250 Watts	1150 Watts
G3 LiPo Light	CX/VX 1600	VX 2200	VX 2200	VX 2600	VX 2600	VX 3300	VX 2600	VX 2600
G3 LiPo Duration	CX 2500	CX 3300	CX 3300	CX 4000	CX 4000	CX 5000	CX 5000	CX 5000
Atlas ESC Suggested	25A~45A	30A~60A	30A~45A	45A~70A	45A~60A	60A~120A	60A~90A	45A~70A
Replaces "Z"	Z3007 / Z3013	Z3013 / Z3019		Z3019 / Z3025		Z3025		