

HP-P1913-06 DIRECT DRIVE (torque motor with 3.0mm shaft)Tested with DC Power Supply @ 3.5V/ Cell > **2S 7.0V**

Battery Equivalent	Prop	Volts	Amps	RPM	Watts	MPH	KPH	Pitch
LVX0800-2S	APC 6 ~5.5E	7.0	6.8	10,200	47.6	53	85	5.5
LVX0800-2S	APC 7 ~4E	7.0	8.6	9,870	60.2	@	@	@
LVX0800-2S	APC 7 ~5E	7.0	9.8	9,450	68.6	45	72	5
LVX0800-2S	APC 8 ~4E	7.0	11.5	8,970	80.5	34	55	4
LVX1200-2S	APC 8 ~6E	7.0	16.4	7,845	114.8	45	72	6
LVX1200-2S	APC 9 ~4.5E	7.0	16.5	8,100	115.5	35	56	4.5
LVX1200-2S	APC 8 ~3.8SF	7.0	13.2	8,775	92	32	51	3.8

Tested with DC Power Supply @ 3.5V/ Cell > **3S 10.5V**

Battery Equivalent	Prop	Volts	Amps	RPM	Watts	MPH	KPH	Pitch
LVX0800-3S	APC 6 ~4E	10.5	9.3	15,030	98	57	92	4
LVX0800-3S	APC 6 ~5.5E	10.5	12.1	14,130	127.05	74	118	5.5
LVX1200-3S	APC 7 ~4E	10.5	16.3	13,230	171.15	50	81	4
LVX1500-3S	APC 7 ~5E	10.5	18.3	12,720	192.15	60	97	5
LVX0800-3S	APC 400 EP 5.0x5.0	10.5	8.2	15,480	86.1	73	118	5
LVX0800-3S	APC 400 EP	10.5	9.0	15,210	94.5	68	110	4.75
LVX0800-3S	APC 400 EP 5.5x4.5	10.5	9.5	15,060	99.75	64	103	4.5