

HP-Z2205-34					
Power Source	Prop	Volts	Amps	RPM	Watts
600W PS	APC7x5SF	6.7	8.1	8565	54
		7.7	10.1	9360	77
	APC8x3.8SF	6.7	10.3	7560	69
	GR7.5x4 Fold	6.7	8.4	8340	56
		7.7	10.5	9150	80
ET-HPV2-0700-2S	APC7x5SF	6.65	7.8	9210	52
ET-HPV2-1250-2S	APC7x5SF	7.04	8.6	8880	60
600W PS	APC5.1x4.5 E	6.7	4.6	9540	31
		7.7	5.5	10740	42
		8.8	6.7	11970	59
		9.9	8.2	12990	81
		10.1	8.6	13200	87
		11	9.6	14190	105
	APC6x4 E	6.7	4.3	9570	29
		7.7	5.4	10830	42
		8.8	6.7	12120	59
		9.9	7.9	13260	78
		10.1	8.2	13440	83
		11	9.3	14280	102
	GR6x3 Fold	6.7	5.3	9060	36
		7.7	6.5	10230	50
		8.8	7.9	11310	70
		9.9	9.6	12270	95
		10.1	9.9	12510	100
ET-HPV2-0700-2S	APC7x5SF	6.51	7.2	8220	47
ET-HPV2-1250-2S	APC7x5SF	6.95	8	8610	56

HP-Z2205-38				
Prop	Volts	Amps	RPM	Watts In
APC 7x5SF	6.7	5.8	7890	39W
	7.7	7.2	8715	55W
	8.8	9.1	9600	80W
APC 8x3.8SF	6.7	7.7	7035	51W
	7.7	9.2	7650	71W
GR 7.5x4 Fold	6.7	6.4	7695	42W
	7.7	7.9	8580	61W
	8.8	9.5	9480	83W
GR 8x4.5 Fold	6.7	8.2	7110	55W

HP-Z2205-46 Initial Prop Tests					
Battery Type	Prop	V	A	RPM	Watts In
ET-HPV2-700-2S	GWS 7x6 SF	7.3	5.4	6660	39.4
	GWS 8x4.3 SF	7.2	5.1	6705	36.7
	GWS 9x4.7 SF	6.8	6.7	5295	45.6
	GWS 9x5DD	7.0	6.0	5865	42.0

ET-HPV2-700-3S	GWS 7x3.5DD	11.3	4.6	11790	52.0
	GWS 8x4DD	10.7	7.5	9630	80.3